



POLYCAB INDIA LIMITED

PCC LP No. 05/2021-22 Dtd : 11th October 2021

List of Products Covered in Our PCC LP

Aluminium Armoured / Unarmoured Cables

Copper Armoured / Unarmoured Cables

HT Cables

Instrumentation Cables

Rubber Cables

JFTC Unarmoured/Armoured Cables & Telephone Dry Armoured Cables

RS 485 Cables

Fire Survival Cables

FS Aluminium Cables



POLYCAB INDIA LIMITED

PCC LP No. 05/2021-22 Dtd : 11th October 2021

"POLYCAB" Brand Power Cables, Solid Aluminum conductor up to 10 sqmm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape/Extruded Innersheathed for Multicore Cables , Armour (Aluminium wire for single core up to 70 sqmm balance Aluminium strip, Galvanised wire for cables upto 2x10 sqmm, 3x10 sqmm,4x6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 sheathed, 650/1100V grade as per IS 7098(Part 1) 1988

Aluminium Armoured

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	1 Core	2 Core	3 Core	3.5 Core	4 Core
	A2XWaY / A2XFaY	A2XWY / A2XFY	A2XWY / A2XFY	A2XFY	A2XWY / A2XFY
2.5		112	125		146
4		129	147		171
6		151	174		197
10		183	219		236
16	124	208	226		279
25	162	242	304	352	376
35	192	299	396	435	480
50	232	370	518	562	639
70	297	494	666	755	858
95	321	633	861	968	1081
120	388	756	1026	1204	1330
150	457	911	1267	1402	1609
185	559	1100	1553	1774	2022
240	729	1429	1963	2259	2532
300	897	1741	2454	2748	3141
400	1131	2142	3140	3535	4076
500	1382	2839	3937	4535	5279
630	1701	3573	5231	6183	7105
800	2120				
1000	2678				

EXTRA FOR SPECIAL CONSTRUCTION:

a) Round Wire Armouring	
- 2 x 16 & above	30%
- 3 x 16 & 3.5CX25 & above	30%
- 4 x 10 & above	30%
- For Single core 95 & above	30%
b) Stranding 10 sq.mm and below	10%
c) Extruded PVC Innersheath Up 50	7.5%
Extruded PVC Innersheath 70 & Above	4%
d) HR PVC Insulation	15%
e) HR PVC Inner Sheath	7.5%
f) HR PVC Outer Sheath	7.5%
g) Oxygen Index (FR)	4%
h) PVC Insulated Cables	12%

Cable Size (Sq.mm)	FRLS Loading Factor		LSZH	
	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
		Armoured		
		Power (Al.)		
Upto 16	15%	11.5%	22.5%	30%
25 - 50	11.5%	11.5%	18%	22.5%
70 & above	7.5%	7.5%	22.5%	18%
		Power Single Core (Al.)		
Upto 16	-N.A-	15%	-N.A-	37.5%
25 - 50	-N.A-	15%	-N.A-	30%
70 & above	-N.A-	11.5%	-N.A-	26%

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.



POLYCAB INDIA LIMITED

PCC LP No. 05/2021-22 Dtd : 11th October 2021

"POLYCAB" Brand Power Cables, Solid Aluminum conductor up to 10 sqmm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape/Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 sheathed, 650/1100V grade as per IS 7098(Part 1) 1988

Aluminium Unarmoured

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	1 Core	2 Core	3 Core	3.5 Core	4 Core
	A2XY	A2XY	A2XY	A2XY	A2XY
4		74	95		111
6		93	118		136
10		130	159		178
16	68	143	179		223
25	106	191	263	330	347
35	129	262	359	397	430
50	167	320	451	516	575
70	221	441	619	708	813
95	283	545	794	908	997
120	339	667	972	1165	1195
150	408	796	1192	1371	1506
185	500	960	1462	1729	1853
240	606	1276	1872	2090	2411
300	756	1559	2319	2657	2887
400	948	1945	2870	3376	3910
500	1241	2370	3752	4373	4996
630	1558	3018	5029	5939	6804
800	1979				
1000	2545				

EXTRA FOR SPECIAL CONSTRUCTION:

a) Stranding 10 sq.mm and below	10%
b) Extruded PVC Innersheath Up 50	7.5%
Extruded PVC Innersheath 70 & Above	4%
c) HR PVC Insulation	15%
d) HR PVC Inner Sheath	7.5%
e) HR PVC Outer Sheath	7.5%
f) Oxygen Index (FR)	4%
g) PVC Insulated Cables	12%

Cable Size (Sq.mm)	FRLS Loading Factor		LSZH	
	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
		Unarmd.		
		Power (Al.)		
Upto 16	15%	11.5%	22.5%	30%
25 - 50	11.5%	11.5%	18%	22.5%
70 & above	7.5%	7.5%	22.5%	18%
		Power Single Core (Al.)		
Upto 16	-N.A-	15%	-N.A-	37.5%
25 - 50	-N.A-	15%	-N.A-	30%
70 & above	-N.A-	12%	-N.A-	26%

• The above rates are exclusive of GST which shall be charged extra.

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.



POLYCAB INDIA LIMITED

PCC LP No. 05/2021-22 Dtd : 11th October 2021

"POLYCAB" Brand Power/Control Copper Cables, Solid Copper conductor upto 6sqmm balance Stranded, XLPE Insulated, cores laid up, PVC tape innersheathed for Multicore Cables, Unarmoured/Armour (Glavanised wire for cables up to 10 x 1.5 sqmm, 8 x 2.5 sqmm, 2 x 10 sqmm, 3 x 10 sqmm, 4 x 6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Armoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	4 Core	5 Core	6 Core	7 Core
	2XWaY / 2XFaY	2XWY / 2XFY	2XWY / 2XFY	2XFY	2XWY / 2XFY	2XWY / 2XFY	2XWY / 2XFY
4		240	316	410	512	607	695
6		329	442	596	717	948	1080
10		522	713	898	1163		
16	442	688	1013	1328	1764		

Control Cables (Rate in Rs. Per Mtr.)

Number of Cores	2XWY/2XFY		Number of Cores	2XWY/2XFY	
	1.5 Sq.mm.	2.5 Sq.mm.		1.5 Sq.mm.	2.5 Sq.mm.
2	135	185	14	541	839
3	167	229	16	601	946
4	203	286	19	704	1084
5	246	343	24	881	1360
6	275	406	27	978	1519
7	305	460	30	1075	1705
8	353	528	37	1308	2090
10	426	603	44	1590	2582
12	473	706	61	2170	3521

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	4%
D) Round Wire Armouring	
1C x 95 sq. mm & above	9%
1.5 sq.mm - 12 core & above	18%
2.5 sq.mm - 9 core & above	18%
10 sq.mm - 4 core & above	18%
16 sq.mm - 2 core & above	18%
16 sq.mm - 3 core & above	18%
E) OXYGEN INDEX (FR)	4%
F) HR PVC Insulatoin	10%
HR I/S & O/S	7.5% Each
G) FRLS Loading-Power Cable (upto 6 Sq.mm.)	11.50%
FRLS Loading-Power Cable (10 Sq.mm. & above)	6%
H) PVC Insulated Cables	7.5%

FRLS Loading Factor- Control Cable			LSZH	
Cores	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
		Armoured		
2 to 4 Core	7.5%	9%	22.5%	22.5%
5 to 10 Core	7.5%	6%	22.5%	22.5%
12 & Above	7.5%	6%	18%	18%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994,with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.



POLYCAB INDIA LIMITED

PCC LP No. 05/2021-22 Dtd : 11th October 2021

"POLYCAB" Brand Power/Control Copper Cables, Solid/Stranded Copper conductor, XLPE Insulated, cores laid up, PVC tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Unarmoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	4 Core
	2XY	2XY	2XY	2XY
4		204	285	357
6		291	408	521
10		503	689	814
16	370	629	971	1239

Control Cables (Rate in Rs. Per Mtr.)

Number of Cores	2XY		Number of Cores	2XY	
	1.5 Sq.mm.	2.5 Sq.mm.		1.5 Sq.mm.	2.5 Sq.mm.
2	99	143	14	448	798
3	127	191	16	532	908
4	163	250	19	629	1045
5	202	308	24	798	1322
6	226	349	27	879	1463
7	259	418	30	1030	1582
8	310	481	37	1241	1956
10	386	547	44	1466	2349
12	402	674	61	2066	3203

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	4%
D OXYGEN INDEX (FR)	4%
E) HR PVC Insulation	10%
HR PVC I/S & O/S	7.5% Each
F) FRLS Loading-Power Cable (upto 6 Sq.mm.)	11.50%
FRLS Loading-Power Cable (10 Sq.mm. & above)	6%
G) PVC Insulated Cables	7.5%

FRLS Loading Factor- Control Cable			LSZH	
Cores	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
Unarmd				
2 - 4	7.5%	9%	22.5%	22.5%
5 - 10	7.5%	6%	22.5%	22.5%
12 & Above	7.5%	6%	18%	18%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994, with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.



POLYCAB INDIA LIMITED

PCC LP No. 05/2021-22 Dtd : 11th October 2021

"POLYCAB" Brand Power/Control Copper Cables, Solid Copper conductor upto 6sqmm balance Stranded, XLPE Insulated, cores laid up, PVC tape innersheathed for Multicore Cables, Unarmoured/Armour (Galvanised wire for cables up to 10 x 1.5 sqmm, 8 x 2.5 sqmm, 2 x 10 sqmm, 3 x 10 sqmm, 4 x 6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Armoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	3.5 Core	4 Core	5 Core
	2XWaY / 2XFaY	2XWY / 2XFY	2XWY / 2XFY	2XFY	2XWY / 2XFY	2XWY / 2XFY
25	638	1089	1582	1877	2073	2678
35	842	1484	2135	2496	2926	4005
50	1162	1972	2872	3425	3810	5460
70	1622	2752	4159	4860	5669	
95	2045	3678	5763	6721	7661	
120	2609	4510	7375	8725	9760	
150	3198	5648	8457	10619	12396	
185	3911	6992	11366	13414	15260	
240	4986	9007	14884	17384	19848	
300	6298	11407	18664	21730	24851	
400	8449	15519	25206	29072	33867	
500	10450					
630	13136					
800	16628					
1000	20901					

POLYCAB Brand Power/Control Copper Cables, Solid/Stranded Copper conductor, XLPE Insulated, cores laid up, PVC tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Unarmoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	3.5 Core	4 Core	
	2XY	2XY	2XY	2XY	2XY	
25	556	1054	1495	1649	1947	
35	740	1410	1997	2354	2776	
50	1039	1898	2702	3281	3562	
70	1461	2544	3947	4674	5424	
95	1953	3471	5643	6688	7400	
120	2512	4367	6895	8586	9332	
150	3090	5465	8095	10245	12139	
185	3828	6742	10708	12678	15180	
240	4931	8632	14314	16799	19654	
300	6202	10755	17661	20649	23653	
400	8155	14356	23150	26725	31720	
500	10380					
630	13067					
800	16552					
1000	20692					

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	4%
D) Round Wire Armouring	
1C x 95 sq. mm & above	9%
10 sq.mm - 4 core & above	18%
16 sq.mm - 2 core & above	18%
16 sq.mm - 3 core & above	18%
E) OXYGEN INDEX (FR)	4%
F) HR PVC Insulation	10%
HR I/S & O/S	7.5% Each
G) FRLS Loading-Power Cable (10 Sq.mm. & above)	6%
H) PVC Insulated Cables	7.5%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, it may vary within the prescribed limit of IS:8130-1994, with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.



POLYCAB INDIA LIMITED

PCC LP No. 05/2021-22 Dtd : 11th October 2021

"POLYCAB" Brand Stranded Compact Circular Aluminium Conductor, Conductor Screen With Extruded Semi Conducting Compound, XLPE Insulated, Insulation Screening with extruded Semi Conducting Compound in combination with Copper Tape, cores laid up, innersheath of PVC tape, galvanised flat steel strip armoured and overall PVC Sheathed Cable conforming to IS 7098 / (PART-II) 1985 with latest amendments.

3 Core HT Cables

Size in Sq.mm.	(Rate in Rs. Per Mtr.)					
	3.3 KV (UE) / 6.6 KV (E)	6.6 KV (UE) / 11 KV (E)	11 KV (UE)	22 KV (E)	33 KV (E)	33 KV (UE)
35		945				
50		1085				
70	1211	1289				
95	1412	1543	2039	2138	2826	
120	1664	1781	2344	2419	3103	
150	1894	1997	2582	2704	3427	3910
185	2198	2332	2931	3048	3796	4343
240	2674	2807	3453	3578	4327	4908
300	3200	3329	3991	4113	4886	5502
400	3975	4066	4728	4934	5685	6363

EXTRA FOR SPECIAL CONSTRUCTION:

1) Extruded PVC Inner Sheath	4.5%
2) Pressure Extruded PVC Innersheath	19.5%
3) Round Wire Armouring - Up to 11 KV (E)	30%
11 KV (UE) & Above	33%
4) FRLS PVC Inner Sheath	7.5%
5) FRLS PVC Outer Sheath	7.5%
6) FR Sheath with Oxygen Index	4.5%

• The above rates are exclusive of GST which shall be charged extra.

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

**POLYCAB INDIA LIMITED**

PCC LP No. 05/2021-22 Dtd : 11th October 2021

"POLYCAB" Brand Stranded Compact Circular Aluminium Conductor, Conductor Screen with extruded semi conducting compound, XLPE insulated, insulation screening with extruded semi conducting compound in combination with Copper tape, AL flat strip / round armoured and overall PVC sheathed cable conforming to IS 7098 / (PART-II) 1985 with latest amendments.

1 Core HT Cables

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	3.3 KV (UE) / 6.6 KV (E)		6.6 KV (UE) / 11 KV (E)		11 KV (UE)		22 KV (E)		33 KV (E)		33 KV (UE)	
	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured
240	952	998	1046	1098	1184	1247	1212	1276	1558	1642	1785	1880
300	1090	1150	1200	1266	1349	1419	1380	1453	1842	1942	1983	2089
400	1325	1397	1438	1513	1602	1685	1637	1722	2114	2220	2237	2353
500	1691	1782	1753	1842	2012	2116	2012	2116	2491	2624	2596	2736
630	2042	2152	2098	2207	2377	2499	2377	2499	2896	3048	3016	3173
800	2540	2670	2574	2784	2847	2998	2847	2998	3428	3607	3578	3762
1000	3004	3162	3299	3475	3529	3711	3529	3711	4194	4398	4510	4745

EXTRA FOR SPECIAL CONSTRUCTION:

1) FRLS PVC Inner Sheath	11.5%
2) FRLS PVC Outer Sheath	7.5%
3) Oxygen Index	4.5%

• The above rates are exclusive of GST which shall be charged extra.

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

**POLYCAB INDIA LIMITED**

PCC LP No. 05/2021-22 Dtd : 11th October 2021

POLYCAB INSTRUMENTATION CABLESStr/Solid Cu PVC/XLPE Insulated Core/Pair/Triad/Quad laid up together with Al (Inner sheathed GI Steel Wire Mylar/Drain Wire)
Round/Strip Armoured PVC Outer Sheathed Instrumentation**OVERALL SHIELDED - ARMOURED INSTRUMENTATION CABLES**

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
CORE	2	0.5	110	0.75	127	1	143	1.5	171	2.5	234
CORE	3	0.5	131	0.75	159	1	180	1.5	223	2.5	309
CORE	4	0.5	148	0.75	177	1	209	1.5	261	2.5	373
CORE	5	0.5	165	0.75	204	1	240	1.5	306	2.5	445
CORE	6	0.5	186	0.75	234	1	281	1.5	353	2.5	527
CORE	7	0.5	201	0.75	257	1	309	1.5	403	2.5	603
CORE	8	0.5	226	0.75	289	1	349	1.5	460	2.5	684
CORE	10	0.5	261	0.75	341	1	417	1.5	553	2.5	840
CORE	12	0.5	295	0.75	387	1	475	1.5	642	2.5	952
CORE	14	0.5	336	0.75	434	1	542	1.5	748	2.5	1122
CORE	16	0.5	368	0.75	484	1	604	1.5	827	2.5	1255
CORE	19	0.5	416	0.75	552	1	700	1.5	946	2.5	1484
CORE	24	0.5	503	0.75	666	1	844	1.5	1172	2.5	1849
PAIR	1	0.5	110	0.75	127	1	143	1.5	171	2.5	234
PAIR	2	0.5	161	0.75	194	1	224	1.5	276	2.5	394
PAIR	3	0.5	194	0.75	242	1	289	1.5	362	2.5	536
PAIR	4	0.5	231	0.75	294	1	355	1.5	465	2.5	696
PAIR	5	0.5	268	0.75	347	1	420	1.5	562	2.5	853
PAIR	6	0.5	308	0.75	399	1	488	1.5	656	2.5	990
PAIR	7	0.5	339	0.75	441	1	551	1.5	756	2.5	1134
PAIR	8	0.5	378	0.75	499	1	620	1.5	838	2.5	1276
PAIR	10	0.5	455	0.75	599	1	751	1.5	1022	2.5	1570
PAIR	12	0.5	515	0.75	672	1	875	1.5	1197	2.5	1848
PAIR	14	0.5	567	0.75	785	1	992	1.5	1384	2.5	2129
PAIR	16	0.5	646	0.75	866	1	1121	1.5	1544	2.5	2420
PAIR	19	0.5	735	0.75	1024	1	1305	1.5	1806	2.5	2835
PAIR	24	0.5	919	0.75	1284	1	1625	1.5	2271	2.5	3563
TRIAD	1	0.5	133	0.75	161	1	182	1.5	225	2.5	311
TRIAD	2	0.5	223	0.75	275	1	306	1.5	396	2.5	572
TRIAD	3	0.5	275	0.75	348	1	398	1.5	522	2.5	773
TRIAD	4	0.5	331	0.75	426	1	497	1.5	656	2.5	973
TRIAD	5	0.5	381	0.75	506	1	589	1.5	794	2.5	1183
TRIAD	6	0.5	439	0.75	586	1	690	1.5	918	2.5	1390
TRIAD	7	0.5	485	0.75	649	1	772	1.5	1034	2.5	1582
TRIAD	8	0.5	546	0.75	714	1	864	1.5	1173	2.5	1806
TRIAD	10	0.5	648	0.75	884	1	1049	1.5	1444	2.5	2226
TRIAD	12	0.5	737	0.75	1017	1	1229	1.5	1686	2.5	2636
TRIAD	14	0.5	838	0.75	1162	1	1406	1.5	1937	2.5	3035
TRIAD	16	0.5	929	0.75	1295	1	1579	1.5	2195	2.5	3441
TRIAD	19	0.5	1073	0.75	1504	1	1839	1.5	2564	2.5	4035
TRIAD	24	0.5	1328	0.75	1882	1	2301	1.5	3229	2.5	5078
QUAD	1	0.5	154	0.75	186	1	216	1.5	269	2.5	383



POLYCAB INDIA LIMITED

PCC LP No. 05/2021-22 Dtd : 11th October 2021

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad/Quad laid up together with Al Inner sheathed Mylar/Drain Wire PVC Inner Sheathed Unarmoured PVC Outer Sheathed Instrumentation Cable.

OVERALL SHIELDED - UNARMOURED INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	1	0.5	69	0.75	84	1	100	1.5	119	2.5	164
PAIR	2	0.5	110	0.75	137	1	164	1.5	231	2.5	314
PAIR	3	0.5	144	0.75	183	1	231	1.5	299	2.5	448
PAIR	4	0.5	164	0.75	231	1	299	1.5	381	2.5	581
PAIR	5	0.5	216	0.75	284	1	417	1.5	463	2.5	716
PAIR	6	0.5	247	0.75	314	1	448	1.5	565	2.5	844
PAIR	7	0.5	267	0.75	362	1	463	1.5	629	2.5	978
PAIR	8	0.5	299	0.75	400	1	547	1.5	716	2.5	1113
PAIR	10	0.5	362	0.75	516	1	663	1.5	897	2.5	1390
PAIR	12	0.5	435	0.75	593	1	781	1.5	1062	2.5	1638
PAIR	14	0.5	480	0.75	683	1	897	1.5	1210	2.5	1887
PAIR	16	0.5	565	0.75	761	1	1028	1.5	1390	2.5	2154
PAIR	19	0.5	647	0.75	909	1	1193	1.5	1623	2.5	2533
PAIR	24	0.5	797	0.75	1127	1	1488	1.5	2040	2.5	3212
TRIAD	1	0.5	92	0.75	104	1	132	1.5	162	2.5	237
TRIAD	2	0.5	152	0.75	187	1	232	1.5	300	2.5	445
TRIAD	3	0.5	204	0.75	249	1	316	1.5	417	2.5	630
TRIAD	4	0.5	251	0.75	313	1	405	1.5	533	2.5	823
TRIAD	5	0.5	302	0.75	379	1	496	1.5	656	2.5	1022
TRIAD	6	0.5	353	0.75	448	1	583	1.5	781	2.5	1211
TRIAD	7	0.5	400	0.75	506	1	664	1.5	893	2.5	1393
TRIAD	8	0.5	453	0.75	579	1	757	1.5	1028	2.5	1589
TRIAD	10	0.5	554	0.75	713	1	947	1.5	1273	2.5	1975
TRIAD	12	0.5	647	0.75	844	1	1114	1.5	1503	2.5	2343
TRIAD	14	0.5	739	0.75	971	1	1283	1.5	1735	2.5	2712
TRIAD	16	0.5	846	0.75	1099	1	1457	1.5	1975	2.5	3099
TRIAD	19	0.5	987	0.75	1285	1	1709	1.5	2318	2.5	3654
TRIAD	24	0.5	1234	0.75	1614	1	2145	1.5	2937	2.5	4602
QUAD	1	0.5	100	0.75	125	1	160	1.5	216	2.5	314

**POLYCAB INDIA LIMITED**

PCC LP No. 05/2021-22 Dtd : 11th October 2021

POLYCAB INSTRUMENTATION CABLES**Str/Solid Cu PVC/XLPE Insulated Pair/Triad laid up together with Al Mylar/Drain Wire Inner sheathed, GI Steel Wire Round/Strip Armoured PVC Outer Sheathed Instrumentation Cables****INDIVIDUAL & OVERALL SHIELDED - ARMoured INSTRUMENTATION CABLES**

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	2	0.5	222	0.75	247	1	281	1.5	343	2.5	474
PAIR	3	0.5	285	0.75	317	1	371	1.5	457	2.5	644
PAIR	4	0.5	340	0.75	387	1	453	1.5	572	2.5	796
PAIR	5	0.5	397	0.75	456	1	541	1.5	664	2.5	961
PAIR	6	0.5	439	0.75	530	1	611	1.5	783	2.5	1119
PAIR	7	0.5	500	0.75	586	1	698	1.5	883	2.5	1273
PAIR	8	0.5	569	0.75	647	1	781	1.5	1000	2.5	1451
PAIR	10	0.5	672	0.75	791	1	952	1.5	1223	2.5	1781
PAIR	12	0.5	751	0.75	919	1	1090	1.5	1428	2.5	2037
PAIR	14	0.5	869	0.75	1034	1	1261	1.5	1630	2.5	2410
PAIR	16	0.5	977	0.75	1164	1	1416	1.5	1838	2.5	2727
PAIR	19	0.5	1116	0.75	1338	1	1636	1.5	2146	2.5	3187
PAIR	24	0.5	1390	0.75	1681	1	2056	1.5	2707	2.5	4009
TRIAD	2	0.5	272	0.75	314	1	355	1.5	442	2.5	610
TRIAD	3	0.5	340	0.75	402	1	464	1.5	588	2.5	834
TRIAD	4	0.5	415	0.75	498	1	576	1.5	722	2.5	1059
TRIAD	5	0.5	486	0.75	589	1	691	1.5	882	2.5	1300
TRIAD	6	0.5	563	0.75	672	1	794	1.5	1033	2.5	1526
TRIAD	7	0.5	622	0.75	750	1	890	1.5	1169	2.5	1734
TRIAD	8	0.5	695	0.75	861	1	1011	1.5	1335	2.5	1978
TRIAD	10	0.5	836	0.75	1041	1	1238	1.5	1637	2.5	2458
TRIAD	12	0.5	967	0.75	1210	1	1447	1.5	1912	2.5	2881
TRIAD	14	0.5	1090	0.75	1374	1	1661	1.5	2207	2.5	3319
TRIAD	16	0.5	1225	0.75	1550	1	1864	1.5	2497	2.5	3766
TRIAD	19	0.5	1420	0.75	1801	1	2186	1.5	2936	2.5	4413
TRIAD	24	0.5	1781	0.75	2266	1	2758	1.5	3668	2.5	5585



POLYCAB INDIA LIMITED

PCC LP No. 05/2021-22 Dtd : 11th October 2021

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad laid up together with Al Mylar/Drain Wire Inner sheathed Unarmoured PVC Outer Sheathed Instrumentation Cable.

INDIVIDUAL & OVERALL SHIELDED - UNARMoured INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	2	0.5	144	0.75	164	1	202	1.5	247	2.5	349
PAIR	3	0.5	183	0.75	231	1	284	1.5	349	2.5	499
PAIR	4	0.5	231	0.75	284	1	349	1.5	448	2.5	647
PAIR	5	0.5	284	0.75	349	1	435	1.5	547	2.5	797
PAIR	6	0.5	333	0.75	417	1	516	1.5	647	2.5	947
PAIR	7	0.5	381	0.75	463	1	581	1.5	729	2.5	1078
PAIR	8	0.5	435	0.75	530	1	663	1.5	844	2.5	1243
PAIR	10	0.5	530	0.75	663	1	828	1.5	1045	2.5	1523
PAIR	12	0.5	616	0.75	781	1	962	1.5	1222	2.5	1822
PAIR	14	0.5	729	0.75	897	1	1127	1.5	1424	2.5	2103
PAIR	16	0.5	814	0.75	1012	1	1262	1.5	1623	2.5	2401
PAIR	19	0.5	947	0.75	1193	1	1488	1.5	1905	2.5	2834
PAIR	24	0.5	1193	0.75	1488	1	1872	1.5	2401	2.5	3563
TRIAD	2	0.5	196	0.75	222	1	270	1.5	340	2.5	490
TRIAD	3	0.5	261	0.75	302	1	373	1.5	471	2.5	693
TRIAD	4	0.5	331	0.75	387	1	480	1.5	614	2.5	909
TRIAD	5	0.5	400	0.75	468	1	583	1.5	748	2.5	1118
TRIAD	6	0.5	464	0.75	552	1	691	1.5	899	2.5	1328
TRIAD	7	0.5	527	0.75	629	1	791	1.5	1028	2.5	1526
TRIAD	8	0.5	599	0.75	727	1	909	1.5	1172	2.5	1743
TRIAD	10	0.5	748	0.75	895	1	1122	1.5	1451	2.5	2178
TRIAD	12	0.5	878	0.75	1050	1	1323	1.5	1713	2.5	2585
TRIAD	14	0.5	1007	0.75	1210	1	1526	1.5	1981	2.5	2993
TRIAD	16	0.5	1134	0.75	1371	1	1733	1.5	2251	2.5	3401
TRIAD	19	0.5	1328	0.75	1607	1	2036	1.5	2665	2.5	3982
TRIAD	24	0.5	1664	0.75	2032	1	2575	1.5	3351	2.5	5043



POLYCAB INDIA LIMITED

PCC LP No. 05/2021-22 Dtd : 11th October 2021

ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED ELASTOMERIC SHEATHED CABLES (Rate Per Mtr)

Size	1.5 Sq.mm.	2.5 Sq.mm.	4 Sq.mm.	6 Sq.mm.	10 Sq.mm.	16 Sq.mm.	25 Sq.mm.	35 Sq.mm.	50 Sq.mm.
1 Core						473	687	953	1355
2 Core	125	192	269	405	685	1048	1581	2144	3053
3 Core	166	267	381	573	973	1489	2222	3040	4331
4 Core	217	348	500	759	1281	1949	2914	4000	5742
5 Core	263	453	670						
6 Core	315	494							
7 Core	346	557							
8 Core	400	678							
10 Core	529	837							
12 Core	634	989							
14 Core	720	1142							
16 Core	834	1300							
19 Core	973	1520							
24 Core	1242	1934							

ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED ELASTOMERIC SHEATHED CABLES (Rate Per Mtr)

Size	70 Sq.mm.	95 Sq.mm.	120 Sq.mm.	150 Sq.mm.	185 Sq.mm.	240 Sq.mm.	300 Sq.mm.	400 Sq.mm.	
1 Core	1904	2498	3168	3941	4803	6346	7948	10435	
3 Core	6103	8002	10143	12624	15384	20238	25383	33209	
4 Core	8000	10485	13378	16651	20307	26708	33461	43913	



POLYCAB INDIA LIMITED

PCC LP No. 05/2021-22 Dtd : 11th October 2021

POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED, UNARMOURED POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION

Rate/Mtr.

SIZE	5 PAIR	10 PAIR				
0.5	88	138				

POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED,G.S.TAPE ARMOURED POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION

Rate/Mtr.

SIZE	5 PAIR	10 PAIR	20 PAIR	50 PAIR	100 PAIR	200 PAIR
0.5	126	188	303	640	1190	2313

POLYCAB BRAND SOLID COPPER CONDUCTOR, POLYTHENE INSULATION, TWISTED PAIRS, LAY-UP, EXTRUDED ST1 GREY PVC INNER SHEATH, SINGLE LAYER GS ROUND WIRE ARMOURED, EXT ST1 GREY PVC OUTER SHEATHED TELEPHONE ARMOURED CABLE AS PER BSNL GR/WIR-06/03 MAR 2002

SIZE	5 PAIR	10 PAIR	20 PAIR			
0.5	103	180	313			



POLYCAB INDIA LIMITED

PCC LP No. 05/2021-22 Dtd : 11th October 2021

POLYCAB RS 485 CABLES (Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / Extr. PVC ST1/ Armoured/ PVC ST1 sheathed Cable

Pairs	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	130
	22 AWG	0.32	143
	20 AWG	0.50	160
	18 AWG	0.80	188
	17 AWG	1.00	203
2 Pair	24 AWG	0.205	188
	22 AWG	0.32	210
	20 AWG	0.50	238
	18 AWG	0.80	293
	17 AWG	1.00	320

POLYCAB RS 485 CABLES (Un Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / UnArmoured/ PVC ST1 sheathed Cable

Size	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	80
	22 AWG	0.32	90
	20 AWG	0.50	103
	18 AWG	0.80	128
	17 AWG	1.00	140
2 Pair	24 AWG	0.205	120
	22 AWG	0.32	143
	20 AWG	0.50	165
	18 AWG	0.80	213
	17 AWG	1.00	240



POLYCAB INDIA LIMITED

PCC LP No. 05/2021-22 Dtd : 11th October 2021

POLYCAB RS 485 CABLES (Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / LSZH Extr. PVC ST1/ Armoured/ LSZH sheathed Cable

Pairs	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	143
	22 AWG	0.32	157
	20 AWG	0.50	176
	18 AWG	0.80	207
	17 AWG	1.00	223
2 Pair	24 AWG	0.205	207
	22 AWG	0.32	231
	20 AWG	0.50	262
	18 AWG	0.80	322
	17 AWG	1.00	352

POLYCAB RS 485 CABLES (Un Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / UnArmoured/ LSZH sheathed Cable

Size	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	88
	22 AWG	0.32	99
	20 AWG	0.50	113
	18 AWG	0.80	141
	17 AWG	1.00	154
2 Pair	24 AWG	0.205	132
	22 AWG	0.32	157
	20 AWG	0.50	182
	18 AWG	0.80	234
	17 AWG	1.00	264

Fire Survival Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Xlpe Insulation/Cores Laid up together/FRLS Inner Sheathed/GI Wire Strip Armoured/ FRLS Outsheathed Fire Survival Cables

Rate/Mtr.				
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	276	344		419
2.5	344	440		543
4	405	530		663
6	524	701		887
10	740	1013		1295
16	982	1371		1804
25	1400	2017	2429	2651
35	1863	2703	3124	3567
50	2455	3589	4209	4752
70	3413	5014	5866	6640
95	4486	6604	7714	8753
120	5581	8252	9833	10958
150	6834	10120	11692	13428
185	8444	12515	14650	16602
240	10735	15945	18635	21174
300	13299	19757	23057	26261
400	17312	25754	29849	34235

Fire Survival Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Xlpe Insulation/Cores Laid up together/Zero Halogen Inner Sheathed/GI Wire Strip Armoured/ Zero Halogen Outersheathed Fire Survival Cables

Rate/Mtr.				
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	308	378		459
2.5	378	477		583
4	441	568		706
6	561	741		932
10	785	1058		1346
16	1024	1415		1862
25	1453	2075	2493	2717
35	1920	2767	3193	3642
50	2519	3660	4287	4841
70	3491	5105	5965	6746
95	4575	6702	7823	8870
120	5676	8360	9963	11098
150	6948	10252	11840	13593
185	8570	12671	14827	16795
240	10888	16134	18846	21407
300	13479	19977	23304	26542
400	17537	26035	30164	34581

**POLYCAB INDIA LIMITED**

PCC LP No. 05/2021-22 Dtd : 11th October 2021

Fire Survival Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Cross Linkable Zero Halogen Insulation/Cores Laid up together/Zero Halogen Inner Sheathed/GI Wire Strip Armoured/ Zero Halogen Outersheathed Fire Survival Cables

Rate/Mtr.				
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	320	396		480
2.5	392	495		608
4	454	586		732
6	576	765		963
10	802	1085		1382
16	1044	1448		1903
25	1486	2125	2553	2784
35	1958	2822	3260	3717
50	2567	3733	4375	4938
70	3554	5199	6078	6873
95	4644	6807	7951	9009
120	5760	8487	10121	11268
150	7055	10416	12035	13813
185	8711	12882	15070	17073
240	11055	16387	19143	21743
300	13677	20274	23656	26938
400	17786	26406	30608	35076



POLYCAB INDIA LIMITED

PCC LP No. 05/2021-22 Dtd : 11th October 2021

FS Aluminium Power Cables

Polycab Make Stranded Sector Aluminium Conductor/Wrapped with Mica Tape/Xlpe Insulation/FRLS Inner Sheathed/GI Wire Armoured/FRLS Sheathed FS Aluminium Power Cables

(Rate/Mtr.)

Sq.mm.	3 Core	4 Core
16	490	633
25	660	840
35	799	1031
50	988	1280
70	1350	1757
95	1687	2196
120	2016	2642
150	2399	3143
185	2907	3797
240	3619	4732
300	4355	5716
400	5420	7098